

PRODUCT SUBMITTAL 805

RAUPEX SPEED Mat, Roll



Product: RAUPEX® SPEED Mat, Roll
Date: 01 April 2022 (supersedes 08 March 2016)



Article No.	Description	Weight
320893-100	RAUPEX Speed Mat, 218.83 ft ² (20.21 m ²) Roll	34.4 lb (15.6 kg)

TECHNICAL DESCRIPTION

Material	Length ft (m)	Width ft (m)	Height in (mm)
PE/PP	70.53 (21.5)	3.1 (0.93)	0.06 (1.5)

FUNCTIONAL DESCRIPTION

The RAUPEX SPEED hook-and-loop mat has an adhesive bottom, allowing installation on thermal insulation, concrete and plywood surfaces. The loop part of the "hook-and-loop system" on the mat's upward surface and the hook material on the RAUPEX SPEED O₂ barrier pipe fasten together instantly. The grid pattern on the mat enables fast and accurate pipe layout.

MATERIAL PLANNING

For quick estimating purposes, the following guidelines may be used for estimating the number of rolls needed for your project. This material estimating information is not intended for a particular project, nor as a final drawing requirement or specification, and is only provided as an aid for quick quotation purposes. REHAU LoopCAD® radiant design software is recommended for calculating material lists for a particular project.

	Overpour Area ft ²		Material Estimating Factor	=	Estimated Material Requirements (round up)
Art. 320893-100	_____	x	218.83 ft ² (20.21 m ²)	=	_____ rolls

For updates to this publication, visit na.rehau.com/resourcecenter

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained therefrom. Before using, the user will determine suitability of the information for user's intended use and shall assume all risk and liability in connection therewith.

© 2022 REHAU